


4.5" (0.290" WALL) PRESSURE GROUTED DISPLACEMENT PILE (TORQUE RATING – 35,000 FT-LB)

Notes

- API threaded couplers
- Estimated grout column diameter of 16"
- Grout port at nose of pile, pressure grouted through ID of pile during installation
- Grout shall have a minimum compression strength of 4,000 psi
- Grout shall be pumped below the maximum pressure of 350 psi during installation
- Shaft Material – OCTG pipe – 80 ksi min yield
- Driver Plate Material – Hot rolled low carbon steel per ASTM A572 Grade 50 minimum
- All welds performed by welders certified by AWS code D1.1
- All driver plates formed with nominal 6" pitch
- Products Hot Dipped Galvanized per ASTM A123 following fabrication. Non-galvanized products are designated with a "U" catalog number suffix
- Ultimate mechanical rating for compression loading is 371 kips
- Ultimate mechanical rating for tension loading is 169 kips
- Custom lead and extension lengths and driver plate diameters (used to form a larger or smaller grout column) are available



4.5" PIPE EXTENSIONS	
Catalog Number	L2 (ft)
W45E20	20
W45E15	15
W45E10	10

4.5" PIPE LEADS		
Catalog Number	Driver Plate Diameter (in)	L1 (ft)
W45L20T16	16	20
W45L15T16	16	15
W45L10T16	16	10